



Rainwater Filtration Made-to-Order Skid 175gpm  
at max pressure 125psi with Domestic Backup  
Includes:

- 50 Micron Backwash Filter
- 5 Micron Bag Filter with Stainless Steel Housing
- Carbon Filter with Stainless Steel Housing
- UV Light
- 3" Flange Rainwater Inlet
- 3" Flange Domestic Inlet
- 3" Flange System Outlet
- 1" Flange Drain Line
- 3" Flow Meter
- 3" RPZ
- 3" Domestic Motorized Valve
- RMS 200 Controller - PLC Touchscreen U.L. Listed Control System
- Single Point Power Disconnect Panel
- Pre-Plumbed in Copper Pro Press
- Pre-Wired

Dimensions of 120" L x 60" W x 84" H



RWF-175  
Standard Filtration Skid

ALL GRADES & ELEVATIONS TO BE SITE  
VERIFIED PRIOR TO CONSTRUCTION

CREATED: 2/2019

REV 0

NOT TO SCALE

DRAWING FOR ILLUSTRATIVE PURPOSES ONLY. NOT FOR CONSTRUCTION.  
DIMENSIONS AND LAYOUT SUBJECT TO CHANGE

RAINWATER MANAGEMENT SOLUTIONS, 1-866-653-8337  
WWW.RAINWATERMANAGEMENT.COM